


Encoders



VALIADIS
HELLENIC MOTORS

Incremental encoders

Standard optical	Sendix 5000 / 5020 (shaft / hollow shaft)	Push-pull / RS422 / Open collector
------------------	---	------------------------------------



24one
10 days max.

Due to their sturdy bearing construction in Safety-Lock™ Design, the Sendix 5000 and 5020 offer high resistance against vibration and installation errors.

The rugged housing, high protection level of up to IP67, as well as the wide temperature range of -40 °C up to +85 °C, make this product range the perfect encoder for all applications.

NEW: 24one delivery promise



Safety-Lock™



High rotational speed



Temperature range



High protection level



High shaft load capacity



Shock / vibration resistant



Magnetic field proof



Short-circuit proof



Reverse polarity protection



Optical sensor

Robust performance

- Increased resistance against vibrations and tolerance of installation errors, elimination of machine downtime and repairs thanks to sturdy bearing construction in "Safety-Lock™ Design".
- Ensures highest safety against field breakdowns and is thus suitable also for outside use thanks to its resistant die-cast housing and protection up to IP67.
- Undetachable clamping ring on hollow shaft encoders.
- Wide temperature range, -40 °C ... +85 °C.

NEW:

- Higher shock resistance.
- Higher vibration resistance.
- IP66 and IP67 protection level in one version.

Many variants

- Suitable connection variant for every specific case: cable connection, M12, M23, MIL and Sub-D connector.
- Reliable mounting in a wide variety of installation situations: comprehensive and proven fixing possibilities.
- Compatible with all US and European standards.
- Max. 5000 pulses per revolution.

NEW:

- Double number of standard pulse numbers.
- Variants with connector fitted in the cable – for error-free electrical connection to your control.
- Additional connector variants (M12 / 5-pin, Sub-D).
- Additional standard cable lengths.

Technology in detail

Robust Safety-Lock™ bearing structure



Cables with fitted connector



Undetachable clamping ring

Slotted clamping ring + slotted shaft



Tangential cable outlet



Incremental encoders

Standard optical	Sendix 5000 / 5020 (shaft / hollow shaft)	Push-pull / RS422 / Open collector
------------------	---	------------------------------------

Order code	8.5000	. XXXXX . XXXX	We offer for all encoders configured with the <u>underlined preferential options</u> our free of charge 24one delivery promise.	 10 days max.
Shaft version	Type	a b c d e	Orders placed on working days before 9AM CET are manufactured and ready for dispatch the same day. The 24one delivery promise is limited to 20 pieces per delivery.	

a Flange

- 5 = synchro flange, IP66/IP67 ø 50.8 mm [2"]
- 6 = synchro flange, IP65 ø 50.8 mm [2"]
- 7 = clamping flange, IP66/IP67 ø 58 mm [2.28"]**
- 8 = clamping flange, IP65 ø 58 mm [2.28"]**
- A = synchro flange, IP66/IP67 ø 58 mm [2.28"]¹⁾**
- B = synchro flange, IP65 ø 58 mm [2.28"]¹⁾**
- C = square flange, IP66/IP67 □ 63.5 mm [2.5"]
- D = square flange, IP65 □ 63.5 mm [2.5"]
- G = Euro flange, IP66/IP67 ø 115 mm [4.53"]²⁾

- 1 = servo flange, IP66/IP67 ø 50.8 mm [2"]³⁾
- 2 = servo flange, IP65 ø 50.8 mm [2"]³⁾
- 3 = square flange, IP66/IP67 □ 52.3 mm [2.06"]³⁾
- 4 = square flange, IP65 □ 52.3 mm [2.06"]³⁾
- E = servo flange, IP66/IP67 ø 63.5 mm [2.5"]³⁾
- F = servo flange, IP65 ø 63.5 mm [2.5"]³⁾

b Shaft (ø x L), with flat

- 1 = ø 6 x 10 mm [0.24 x 0.39"]**
- 2 = ø 1/4 x 5/8" (6.35 x 15.875 mm)
- 6 = ø 8 x 15 mm [0.32 x 0.59"]
- 3 = ø 10 x 20 mm [0.39 x 0.79"]**
- 4 = ø 3/8 x 5/8" (9.5 x 15.875 mm)
- B = ø 11 x 33 mm [0.43 x 1.30"], with feather key shaft slot⁴⁾
- 5 = ø 12 x 20 mm [0.47 x 0.79"]
- 7 = ø 1/4 x 7/8"³⁾
- 8 = ø 3/8 x 7/8"³⁾

c Output circuit (with inverted signal) / supply voltage

- 4 = RS422 / 5 V DC**
- 1 = RS422 / 5 ... 30 V DC**
- 2 = push-pull (7272 compatible) / 5 ... 30 V DC**
- 5 = push-pull / 10 ... 30 V DC**

- 3 = open collector / 5 ... 30 V DC³⁾**
- 8 = push-pull (7272 compatible), without capacitor / 5 ... 30 V DC¹⁾³⁾⁶⁾

d Type of connection – cable

- 1 = axial cable, 1 m [3.28'] PVC**
- A = axial cable, special length PVC *)
- 2 = radial cable, 1 m [3.28'] PVC**
- B = radial cable, special length PVC *)

Type of connection – connector

- P = axial M12 connector, 5-pin⁵⁾
- R = radial M12 connector, 5-pin⁵⁾
- 3 = axial M12 connector, 8-pin**
- 4 = radial M12 connector, 8-pin**
- 7 = axial M23 connector, 12-pin**
- 8 = radial M23 connector, 12-pin**
- Y = radial MIL connector, 10-pin**
- W = radial MIL connector, 7-pin⁵⁾**

- 9 = radial MIL connector, 6-pin³⁾⁵⁾

Type of connection – connector with cable

- L = radial cable with M12 connector, 8-pin, special length PVC *)
- M = radial cable with M23 connector, 12-pin, special length PVC *)
- N = radial cable with Sub-D connector, 9-pin, special length PVC *)

*) Available special lengths (connection types A, B, L, M, N):
0.3, 0.5, 1, 2, 3, 4, 5, 6, 8, 10, 12, 15, 20 m [0.98, 1.64, 3.28, 6.56, 9.84, 13.12, 16.40, 19.69, 26.25, 32.80, 39.37, 49.21, 65.62']
order code expansion .XXXX = length in dm
ex.: 8.5000.814A.1024.0030 (for cable length 3 m)

e Pulse rate

- 1, 2, 4, 5, 10, 12, 14, 20, 25, 28, 30, 32, 36, 50, 60, 64, 80, 100, 120, 125, 150, 180, 200, 240, 250, 256, 300, 342, 360, 375, 400, 500, 512, 600, 625, 720, 800, 900, 1000, 1024, 1200, 1250, 1500, 1800, 2000, 2048, 2500, 3000, 3600, 4000, 4096, 5000**
- (e.g. 100 pulses => 0100)

Optional on request

- other pulse rates
- Ex 2/22 (not for type of connection L, M, N)⁷⁾
- surface protection salt spray

Salt spray tested as standard type
(deliverable as from 1 unit)

8.5000.73X4.XXXX-C



1) 24one type only in conjunction with shaft type 1.
2) Only in conjunction with shaft type B.
3) US version.
4) Only in conjunction with flange type G.
5) Without inverted signal.
6) Attention: no CE types!
7) For the cable connection type, cable material PUR.

Incremental encoders

Standard optical	Sendix 5000 / 5020 (shaft / hollow shaft)	Push-pull / RS422 / Open collector
------------------	---	------------------------------------

Order code
Hollow shaft

8.5020
 Type

.	X	X	X	X	.	XXXX
a	b	c	d	e		

We offer for all encoders configured with the underlined preferential options our free of charge 24one delivery promise.
 Orders placed on working days before 9AM CET are manufactured and ready for dispatch the same day. The 24one delivery promise is limited to 20 pieces per delivery.

24one
 10 days max.

a Flange
1 = with spring element, long, IP66/IP67
2 = with spring element, long, IP65
3 = with torque stop, long, IP66/IP67
4 = with torque stop, long, IP65
7 = with stator coupling, IP66/IP67 ø 65 mm [2.56"]
8 = with stator coupling, IP65 ø 65 mm [2.56"]
C = with stator coupling, IP66/IP67 ø 63 mm [2.48"]
D = with stator coupling, IP65 ø 63 mm [2.48"]

 5 = with stator coupling, IP66/IP67 ø 57.2 mm [2.25"] ¹⁾
 6 = with stator coupling, IP65 ø 57.2 mm [2.25"] ¹⁾

b Through hollow shaft
 1 = ø 6 mm [0.24"]
 2 = ø 1/4"
9 = ø 8 mm [0.32"]
 4 = ø 3/8"
3 = ø 10 mm [0.39"]
5 = ø 12 mm [0.47"]
 6 = ø 1/2"
 A = ø 14 mm [0.55"]
8 = ø 15 mm [0.59"]
 7 = ø 5/8"

c Output circuit (with inverted signal) / supply voltage
4 = RS422 / 5 V DC
1 = RS422 / 5 ... 30 V DC
2 = push-pull (7272 compatible) / 5 ... 30 V DC
5 = push-pull / 10 ... 30 V DC

3 = open collector / 5 ... 30 V DC ¹⁾
 8 = push-pull (7272 compatible), without capacitor / 5 ... 30 V DC ¹⁾²⁾

d Type of connection – cable
1 = radial cable, 1 m [3.28'] PVC
 A = radial cable, special length PVC *)
E = tangential cable, 1 m [3.28'] PVC
 F = tangential cable, special length PVC *)

Type of connection – connector
 R = radial M12 connector, 5-pin ³⁾
2 = radial M12 connector, 8-pin
4 = radial M23 connector, 12-pin
 6 = radial MIL connector, 7-pin
7 = radial MIL connector, 10-pin

Type of connection – connector with cable
 H = tangential cable, 0.3 m [0.98'] PVC, incl. M12 connector, 8-pin for central fastening
 L = tangential cable with M12 connector, 8-pin, special length PVC *)
 M = tangential cable with M23 connector, 12-pin, special length PVC *)
 N = tangential cable with Sub-D connector, 9-pin, special length PVC *)

 *) Available special lengths (connection types A, F, L, M, N):
 0.3, 0.5, 1, 2, 3, 4, 5, 6, 8, 10, 12, 15, 20 m [0.98, 1.64, 3.28, 6.56, 9.84, 13.12, 16.40, 19.69, 26.25, 32.80, 39.37, 49.21, 65.62']
 order code expansion .XXXX = length in dm
 ex.: 8.5020.234A.1024.0030 (for cable length 3 m)

e Pulse rate
1, 2, 4, 5, 10, 12, 14, 20, 25, 28, 30, 32, 36, 50, 60, 64, 80, 100, 120, 125, 150, 180, 200, 240, 250, 256, 300, 342, 360, 375, 400, 500, 512, 600, 625, 720, 800, 900, 1000, 1024, 1200, 1250, 1500, 1800, 2000, 2048, 2500, 3000, 3600, 4000, 4096, 5000
 (e.g. 100 pulses => 0100)

Optional on request
 - other pulse rates
 - Ex 2/22 (not for type of connection E, F, H, L, M, N) ⁴⁾
 - surface protection salt spray

Salt spray tested as standard type (deliverable as from 1 unit)

 8.5020.18X2.XXXX-C
 8.5020.1AX2.XXXX-C

1) US version.
 2) Attention: no CE types!
 3) Without inverted signal.
 4) For the cable connection type, cable material PUR.

Incremental encoders

Standard optical		Sendix 5000 / 5020 (shaft / hollow shaft)		Push-pull / RS422 / Open collector	
Mounting accessory for shaft encoders				Order no.	
Coupling	bellows coupling ø 19 mm [0.75"] for shaft 6 mm [0.24"]			8.0000.1102.0606	
	bellows coupling ø 19 mm [0.75"] for shaft 10 mm [0.39"]			8.0000.1102.1010	
Mounting accessory for hollow shaft encoders				Dimensions in mm [inch]	
Cylindrical pin, long		with fixing thread		8.0010.4700.0000	
for flange with spring element (flange type 1 + 2)					
Isolation / adapter inserts for hollow shaft encoders		Thermal and electrical isolation of the encoders (Temperature range -40 °C ... +115 °C [-40 °F ... +239 °F]) Isolation inserts prevent currents from passing through the encoder bearings. These currents can occur when using inverter controlled three-phase or AC vector motors and considerably shorten the service life of the encoder bearings. In addition the encoder is thermally isolated as the plastic does not transfer the heat to the encoder.		D1	
order code				6 mm	
8.5020.X8XX.XXXX				8 mm	
				10 mm	
				12 mm	
				1/4"	
				3/8"	
				1/2"	
				Isolation insert	
				8.0010.4021.0000	
				8.0010.4020.0000	
				8.0010.4023.0000	
				8.0010.4025.0000	
				8.0010.4022.0000	
				8.0010.4024.0000	
				8.0010.4026.0000	
Connection technology				Order no.	
Cordset, pre-assembled		M12 female connector with coupling nut, 8-pin, A coded, straight single ended 2 m [6.56'] PVC cable		05.00.6041.8211.002M	
		M23 female connector with coupling nut, 12-pin, cw single ended 2 m [6.56'] PVC cable		8.0000.6901.0002	
Connector, self-assembly		M12 female connector with coupling nut, 8-pin, A coded, straight (metal)		05.CMB 8181-0	
		M23 female connector with coupling nut, 12-pin, cw		8.0000.5012.0000	
		MIL female connector with coupling nut, 10-pin		8.0000.5062.0000	

Further Kübler accessories can be found at: kuebler.com/accessories

Further Kübler cables and connectors can be found at: kuebler.com/connection-technology

Incremental encoders

Standard optical	Sendix 5000 / 5020 (shaft / hollow shaft)	Push-pull / RS422 / Open collector
------------------	---	------------------------------------

Technical data

Mechanical characteristics

Maximum speed	IP65	12000 min ⁻¹	Weight	approx. 0.4 kg [14.11 oz]		
		6000 min ⁻¹ (continuous)		Protection acc. to EN 60529		
	IP66/IP67	6000 min ⁻¹			without shaft seal	IP65
		3000 min ⁻¹ (continuous)			with shaft seal	IP66/IP67
Mass moment of inertia			Working temperature range	-40 °C ¹⁾ ... +85 °C [-40 °F ¹⁾ ... +185 °F]		
	shaft version	approx. 1.8 x 10 ⁻⁶ kgm ²		Material	shaft stainless steel	
	hollow shaft version	approx. 6 x 10 ⁻⁶ kgm ²	Shock resistance acc. to EN 60068-2-27		3000 m/s ² , 6 ms ²⁾	
Starting torque at 20 °C [68 °F]	IP65	< 0.01 Nm		Vibration resistance acc. to EN 60068-2-6	300 m/s ² , 10 ... 2000 Hz ³⁾	
	IP66/IP67	< 0.05 Nm				
Shaft load capacity	radial	100 N				
	axial	50 N				

Electrical characteristics

Output circuit	RS422 (TTL compatible)	RS422 (TTL compatible)	Push-pull	Push-pull (HTL/TTL universal, 7272 compatible)	Push-pull (7272 compatible, without capacitor)	Open collector (7273)
Order code	1	4	5, 7	2	8	3
Supply voltage	5 ... 30 V DC	5 V DC (±5 %)	10 ... 30 V DC	5 ... 30 V DC	5 ... 30 V DC	5 ... 30 V DC
Power consumption (no load)	typ. 40 mA max. 90 mA	typ. 40 mA max. 90 mA	typ. 50 mA max. 100 mA	typ. 50 mA max. 100 mA	typ. 50 mA max. 100 mA	100 mA
Permissible load / channel	max. +/- 20 mA	max. +/- 20 mA	max. +/- 20 mA	max. +/- 20 mA	max. +/- 20 mA	20 mA sink at 30 V DC
Pulse frequency	max. 300 kHz	max. 300 kHz	max. 300 kHz	max. 300 kHz ⁴⁾	max. 300 kHz	max. 300 kHz
Signal level	HIGH	min. 2.5 V	min +V - 1.0 V	min. +V - 2.0 V	min. +V - 2.0 V	
	LOW	max. 0.5 V	max. 0.5 V	max. 0.5 V	max. 0.5 V	
Rising edge time t_r	max. 200 ns	max. 200 ns	max. 1 µs	max. 1 µs	max. 1 µs	
Falling edge time t_f	max. 200 ns	max. 200 ns	max. 1 µs	max. 1 µs	max. 1 µs	
Short circuit proof outputs ⁵⁾	yes ⁶⁾	yes ⁶⁾	yes	yes	yes ⁶⁾	yes
Reverse polarity protection of the supply voltage	yes	no	yes	no	no	no
UL approval	file no. E224618					
CE compliant acc. to	EMC guideline 2014/30/EU RoHS guideline 2011/65/EU					

1) With connector: -40 °C [-40 °F], cable fixed: -30 °C [-22 °F], cable moved: -20 °C [-4 °F].

2) For MIL connectors: 2500 m/s²

3) For MIL connectors: 100 m/s²

4) Max. recommended cable length 30 m [98.43'].

5) If supply voltage correctly applied.

6) Only one channel allowed to be shorted-out:
at +V= 5 V DC, short-circuit to channel, 0 V, or +V is permitted.
at +V= 5 ... 30 V DC, short-circuit to channel or 0 V is permitted.

Incremental encoders

Standard optical	Sendix 5000 / 5020 (shaft / hollow shaft)	Push-pull / RS422 / Open collector
------------------	---	------------------------------------


Terminal assignment

Output circuit	Type of connection	Cable (isolate unused cores individually before initial start-up)											
1, 2, 3, 4, 5, 8	5000: 1, 2, A, B	Signal:	0 V	+V	0 Vsens	+Vsens	A	$\bar{A}$	B	$\bar{B}$	0	$\bar{0}$	$\perp$
	5020: 1, A, E, F	Core color:	WH	BN	GY PK	RD BU	GN	YE	GY	PK	BU	RD	shield
Output circuit	Type of connection	M12 connector, 5-pin											
1, 2, 3, 4, 5, 8	5000: P, R	Signal:	0 V	+V	A	B	0	$\perp$					
	5020: R	Pin:	1	2	3	4	5	PH ¹⁾					
Output circuit	Type of connection	M12 connector, 8-pin											
1, 2, 3, 4, 5, 8	5000: 3, 4, L	Signal:	0 V	+V	A	$\bar{A}$	B	$\bar{B}$	0	$\bar{0}$	$\perp$		
	5020: 2, H ²⁾ , L	Pin:	1	2	3	4	5	6	7	8	PH ¹⁾		
Output circuit	Type of connection	M23 connector, 12-pin											
1, 2, 3, 4, 5, 8	5000: 7, 8, M	Signal:	0 V	+V	0 Vsens	+Vsens	A	$\bar{A}$	B	$\bar{B}$	0	$\bar{0}$	$\perp$
	5020: 4, M	Pin:	10	12	11	2	5	6	8	1	3	4	PH ¹⁾
Output circuit	Type of connection	MIL connector, 10-pin											
1, 2, 3, 4, 5, 8	5000: Y	Signal:	0 V	+V	+Vsens	A	$\bar{A}$	B	$\bar{B}$	0	$\bar{0}$	$\perp$	
	5020: 7	Pin:	F	D	E	A	G	B	H	C	I	J	
Output circuit	Type of connection	MIL connector, 7-pin											
1, 3, 4, 5, 8	5000: W	Signal:	0 V	+V	+Vsens	A	B	0	$\perp$				
	5020: 6	Pin:	F	D	E	A	B	C	G				
Output circuit	Type of connection	MIL connector, 6-pin											
1, 3, 4, 5, 8	5000: 9	Signal:	0 V	+V	A	B	0	$\perp$					
		Pin:	A	B	E	D	C						
Output circuit	Type of connection	Sub-D connector, 9-pin											
1, 2, 3, 4, 5, 8	5000: N	Signal:	0 V	+V	A	$\bar{A}$	B	$\bar{B}$	0	$\bar{0}$	$\perp$		
	5020: N	Pin:	9	5	1	6	2	7	3	8	PH ¹⁾		

+V: Supply voltage encoder +V DC
 0 V: Supply voltage encoder ground GND (0 V)
 0 Vsens / +Vsens: Using the sensor outputs of the encoder, the voltage present can be measured and if necessary increased accordingly.

A, $\bar{A}$: Incremental output channel A
 B, $\bar{B}$: Incremental output channel B
 0, $\bar{0}$: Reference signal
 PH $\perp$: Plug connector housing (shield)


Top view of mating side, male contact base




M12 connector, 5-pin




M12 connector, 8-pin




M23 connector, 12-pin




MIL connector, 10-pin



MIL connector, 7-pin



MIL connector, 6-pin



Sub-D connector, 9-pin

1) PH = shield is attached to connector housing.
 2) With type of connection H shield is not attached to connector housing.

Incremental encoders

Standard optical	Sendix 5000 / 5020 (shaft / hollow shaft)	Push-pull / RS422 / Open collector
------------------	---	------------------------------------




Dimensions shaft version

Dimensions in mm [inch]

Synchro flange, $\varnothing 50.8$ [2]

Flange type 5 and 6

1 3 x M3, 6 [0.24] deep






MIL-connector version

D	Fit	L
6 [0.24]	h7	10 [0.39]
8 [0.32]	h7	15 [0.59]
10 [0.39]	h7	20 [0.79]
12 [0.47]	h7	20 [0.79]
1/4"	h7	5/8"
3/8"	h7	5/8"
1/4"	h8	7/8"
3/8"	h8	7/8"

Clamping flange, $\varnothing 58$ [2.28]

Flange type 7 and 8

1 3 x M3, 6 [0.24] deep



MIL-connector version

D	Fit	L
6 [0.24]	h7	10 [0.39]
8 [0.32]	h7	15 [0.59]
10 [0.39]	h7	20 [0.79]
12 [0.47]	h7	20 [0.79]
1/4"	h7	5/8"
3/8"	h7	5/8"
1/4"	h8	7/8"
3/8"	h8	7/8"

Incremental encoders

Standard optical	Sendix 5000 / 5020 (shaft / hollow shaft)	Push-pull / RS422 / Open collector
------------------	---	------------------------------------




Dimensions shaft version

Dimensions in mm [inch]

Synchro flange, $\varnothing 58$ [2.28]

Flange type A and B

1 3 x M4, 6 [0.24] deep






MIL-connector version

D	Fit	L
6 [0.24]	h7	10 [0.39]
8 [0.32]	h7	15 [0.59]
10 [0.39]	h7	20 [0.79]
12 [0.47]	h7	20 [0.79]
1/4"	h7	5/8"
3/8"	h7	5/8"
1/4"	h8	7/8"
3/8"	h8	7/8"

Square flange, $\square 63.5$ [2.5]

Flange type C and D



MIL-connector version

D	Fit	L
6 [0.24]	h7	10 [0.39]
8 [0.32]	h7	15 [0.59]
10 [0.39]	h7	20 [0.79]
12 [0.47]	h7	20 [0.79]
1/4"	h7	5/8"
3/8"	h7	5/8"
1/4"	h8	7/8"
3/8"	h8	7/8"

Incremental encoders

Standard optical	Sendix 5000 / 5020 (shaft / hollow shaft)	Push-pull / RS422 / Open collector
------------------	---	------------------------------------


Dimensions shaft version

Dimensions in mm [inch]

Euro flange, ø 115 [4.53]

Flange type G


- 1 Feather key attached



Servo flange, ø 50.8 [2]

Flange type 1 and 2

- 1 4-40 UNC x 6 [0.24] deep
2 6-32 UNC x 5 [0.2] deep



MIL-connector version

D	Fit	L
6 [0.24]	h7	10 [0.39]
8 [0.32]	h7	15 [0.59]
10 [0.39]	h7	20 [0.79]
12 [0.47]	h7	20 [0.79]
1/4"	h7	5/8"
3/8"	h7	5/8"
1/4"	h8	7/8"
3/8"	h8	7/8"

Incremental encoders

Standard optical

Sendix 5000 / 5020 (shaft / hollow shaft)

Push-pull / RS422 / Open collector




Dimensions shaft version

Dimensions in mm [inch]

Square flange, □ 52.3 [2.06]

Flange type 3 and 4

- 1 Ø 4 [0.16]
2 6-32 UNC x 5 [0.2] deep






MIL-connector version

D	Fit	L
6 [0.24]	h7	10 [0.39]
8 [0.32]	h7	15 [0.59]
10 [0.39]	h7	20 [0.79]
12 [0.47]	h7	20 [0.79]
1/4"	h7	5/8"
3/8"	h7	5/8"
1/4"	h8	7/8"
3/8"	h8	7/8"

Servo flange, ø 63.5 [2.5]

Flange type E and F

- ① 6-32 UNC x 5 [0.2] deep



MIL-connector version

D	Fit	L
6 [0.24]	h7	10 [0.39]
8 [0.32]	h7	15 [0.59]
10 [0.39]	h7	20 [0.79]
12 [0.47]	h7	20 [0.79]
1/4"	h7	5/8"
3/8"	h7	5/8"
1/4"	h8	7/8"
3/8"	h8	7/8"

Incremental encoders




Standard optical	Sendix 5000 / 5020 (shaft / hollow shaft)	Push-pull / RS422 / Open collector
------------------	---	------------------------------------

Dimensions hollow shaft version

Dimensions in mm [inch]

Flange with spring element, long Flange type 1 and 2

- 1 3 x M3, 6 [0.24] deep
- 2 Slot spring element, recommendation: cylindrical pin DIN 7, $\varnothing$ 4 [0.16]
- 3 Recommended torque for the clamping ring 0.6 Nm





MIL-connector version

D	Fit
6 [0.24]	H7
8 [0.32]	H7
10 [0.39]	H7
12 [0.47]	H7
14 [0.55]	H7
15 [0.59]	H7
1/4"	H7
3/8"	H7
1/2"	H7
5/8"	H7

Recommended fit for shaft on customer side is g6.

Flange with torque stop, long Flange type 3 and 4

- 1 Recommended torque for the clamping ring 0.6 Nm



D	Fit
6 [0.24]	H7
8 [0.32]	H7
10 [0.39]	H7
12 [0.47]	H7
14 [0.55]	H7
15 [0.59]	H7
1/4"	H7
3/8"	H7
1/2"	H7
5/8"	H7

Recommended fit for shaft on customer side is g6.

Incremental encoders

Standard optical	Sendix 5000 / 5020 (shaft / hollow shaft)	Push-pull / RS422 / Open collector
------------------	---	------------------------------------

Dimensions hollow shaft version

Dimensions in mm [inch]


Flange with stator coupling, ø 65 [2.56]

Flange type 7 and 8

- 1 Recommended torque for the clamping ring 0.6 Nm

D	Fit
6 [0.24]	H7
8 [0.32]	H7
10 [0.39]	H7
12 [0.47]	H7
14 [0.55]	H7
15 [0.59]	H7
1/4"	H7
3/8"	H7
1/2"	H7
5/8"	H7

Recommended fit for shaft on customer side is g6.




Flange with stator coupling, ø 63 [2.48]

Flange type C and D

- 1 Recommended torque for the clamping ring 0.6 Nm

D	Fit
6 [0.24]	H7
8 [0.32]	H7
10 [0.39]	H7
12 [0.47]	H7
14 [0.55]	H7
15 [0.59]	H7
1/4"	H7
3/8"	H7
1/2"	H7
5/8"	H7

Recommended fit for shaft on customer side is g6.




Flange with stator coupling, ø 57.2 [2.25]

Flange type 5 and 6

- 1 Recommended torque for the clamping ring 0.6 Nm

D	Fit
6 [0.24]	H7
8 [0.32]	H7
10 [0.39]	H7
12 [0.47]	H7
14 [0.55]	H7
15 [0.59]	H7
1/4"	H7
3/8"	H7
1/2"	H7
5/8"	H7

Recommended fit for shaft on customer side is g6.



Incremental encoders

**Standard
optical**

Sendix 5000 / 5020 (shaft / hollow shaft)

Push-pull / RS422 / Open collector


Dimensions hollow shaft version

Dimensions in mm [inch]

**Flange with spring element, long and
tangential cable outlet**

Type of connection E, F and H

- 1 3 x M3, 6 [0.24] deep
- 2 Slot spring element,
recommendation:
cylindrical pin DIN 7, $\varnothing$ 4 [0.16]
- 3 Recommended torque for the
clamping ring 0.6 Nm
- 4 Shield is not applied on connector



D	Fit
6 [0.24]	H7
8 [0.32]	H7
10 [0.39]	H7
12 [0.47]	H7
14 [0.55]	H7
15 [0.59]	H7
1/4"	H7
3/8"	H7
1/2"	H7
5/8"	H7

Recommended fit for shaft on customer side is g6.



www.valiadismotors.com